May-09-03

PATENT Atty, Dkt., No. AVIS/1014C

RAY ;

required under 37 CFR 1.321(c) to disclaim the patent term of a single patent application. Applicants are not disclaiming the terms of the issued patents. Applicants are merely disclaiming the term of this one application. As such, only one disclaimer fee is required under 37 CFR 1.321(c) and 37 CFR 1.20(d).

Having addressed all issues set out in the office action, Applicants respectfully submit that the claims are in condition for allowance and respectfully request that the claims be allowed.

Respectfully submitted.

Robb D. Edmonds

Registration No. 46,681

MOSER, PATTERSON & SHERIDAN, L.L.P.

3040 Post Oak Blvd., Suite 1500

Houston, TX 77056

Telephone: (713) 623-4844 Facsimile: (713) 623-4846 Attorney for Applicant(s)

PATENT Atty. Dkt. No. AVIS/1014C

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE SPECIFICATION:

This application is a continuation under 37 C.F.R. §1.53(b) of United States Application No. 09/418,448, filed on October 15, 1999, now Patent No. 6,129,999, which is a continuation-in-part of United States Application No. 09/250,741, filed on February 16, 1999, now Patent No. 6,007,701. This application is also related to copending United States Application No. 09/753,496, filed on January 2, 2001, and United States Application No. 09/664,195, filed on September 18, 2000, now Patent No. 6,398,948.

IN THE CLAIMS:

- (Amended) A method for purifying used oil, comprising:
 mixing the used oil with a phase transfer catalyst in the presence of a base
 compound, wherein the phase transfer catalyst comprises a glycol; and
 removing contaminants from the used oil.
- 31. (Amended) A method for removing contaminants from motor oil, comprising:
 mixing the motor oil with an inorganic base compound;
 mixing the motor oil with a phase transfer catalyst in the presence of the
 inorganic base compound, wherein the phase transfer catalyst comprises a glycol; and
 then

distilling the motor oil at a temperature of about 200°C to about 275°C and a pressure of about 100 torr to about 200 torr.